


Anti-parallel Module

Description:

- 1) A package consists of two inverse parallel SCR chips, which non-repetitive peak off-state voltage is up to 2300V
- 2) Welding by vacuum welding technology, which provide high reliability
- 3) Insulated by silicone gel, provide a insulation voltage of 3000V~

Typical Application:

Soft start, solid state relay, AC/DC switch, temperature control.



Absolute Maximum Ratings (Packaged into V1-A-Pack, unless otherwise specified, $T_{CASE}=25^{\circ}C$)

Parameter	Test Conditions	Symbol	Values			Unit
			18	20	22	
Operating junction temperature range		T_j	-40-125			$^{\circ}C$
Storage temperature range		T_{stg}	-40-125			$^{\circ}C$
Repetitive peak off-state voltage	$T_j=25^{\circ}C$	V_{DRM}	1800	2000	2200	V
Repetitive peak reverse voltage	$T_j=25^{\circ}C$	V_{RRM}	1800	2000	2200	V
Non-repetitive peak off-state voltage	$T_j=25^{\circ}C$	V_{DSM}	1900	2100	2300	V
Non-repetitive peak reverse voltage	$T_j=25^{\circ}C$	V_{RSM}	1900	2100	2300	V
RMS on-state current	$T_C=85^{\circ}C$	$I_{T(RMS)}$	150			A
Peak on-state surge current	$t_p=10ms V_R=0.6V_{RRM}$	I_{TSM}	2200			A
I^2t value for fusing	$t_p=10ms V_R=0.6V_{RRM}$	I^2t	11250			A^2s
Critical rate of rise of on-state current	$I_G=2 \times I_{GT}$	di/dt	150			$A/\mu s$
Insulation voltage	A.C 50Hz(1s/1min)	V_{ISO}	3600/3000			V

Electrical Characteristics (Packaged into V1-A-Pack, unless otherwise specified, $T_{CASE}=25^{\circ}C$)

Parameter	Test Conditions	Symbol	Values	Unit
Peak on-state voltage	$I_T=300A$ $t_p=380\mu s$	V_{TM}	≤ 1.8	V
Threshold voltage	$T_j=125^{\circ}C$	V_{TO}	≤ 0.95	V
Dynamic resistance	$T_j=125^{\circ}C$	R_d	≤ 2.1	m Ω
Repetitive peak off-state current	$V_D=V_{RRM}$ $T_C=25^{\circ}C$	I_{DRM1}	≤ 100	μA
	$T_C=125^{\circ}C$	I_{DRM2}	≤ 30	mA
Repetitive peak reverse current	$V_R=V_{RRM}$ $T_C=25^{\circ}C$	I_{RRM1}	≤ 100	μA
	$T_C=125^{\circ}C$	I_{RRM2}	≤ 30	mA
Triggering gate current	$V_D=12V$ $R_L=30\Omega$	I_{GT}	20-120	mA
Holding current	$I_T=1A$	I_H	≤ 250	mA
Latching current	$I_G=1.2 I_{GT}$	I_L	≤ 300	mA
Triggering gate voltage	$V_D=12V$ $R_L=30\Omega$	V_{GT}	≤ 1.8	V
Non triggering gate voltage	$V_D=V_{DRM}$ $T_j=125^{\circ}C$	V_{GD}	≥ 0.25	V
Critical rate of rise of voltage	$V_D=2/3V_{DRM}$ $T_j=125^{\circ}C$ Gate Open	dv/dt	≥ 1000	V/ μs
Thermal resistance	Junction to case	$R_{th(j-c)}$	0.35	$^{\circ}C/W$

Mechanical Characteristics

Module size	63x31.6mm																																																																																																																																																																																										
Module height	21.6mm																																																																																																																																																																																										
<table border="1"> <thead> <tr> <th rowspan="2">Ref</th> <th colspan="6">Dimensions</th> </tr> <tr> <th colspan="3">Millimeters</th> <th colspan="3">Inches</th> </tr> <tr> <th></th> <th>Min</th> <th>Typ</th> <th>Max</th> <th>Min</th> <th>Typ</th> <th>Max</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>2.85</td> <td>3</td> <td>3.15</td> <td>0.112</td> <td>0.118</td> <td>0.124</td> </tr> <tr> <td>B</td> <td>2.3</td> <td>2.5</td> <td>2.7</td> <td>0.091</td> <td>0.098</td> <td>0.106</td> </tr> <tr> <td>C</td> <td>1.9</td> <td>2.1</td> <td>2.3</td> <td>0.075</td> <td>0.083</td> <td>0.091</td> </tr> <tr> <td>D</td> <td></td> <td></td> <td>6</td> <td></td> <td></td> <td>0.236</td> </tr> <tr> <td>E</td> <td>16.25</td> <td>17</td> <td>17.75</td> <td>0.640</td> <td>0.669</td> <td>0.699</td> </tr> <tr> <td>F</td> <td>0.4</td> <td>0.5</td> <td>0.6</td> <td>0.016</td> <td>0.020</td> <td>0.024</td> </tr> <tr> <td>G</td> <td>20.85</td> <td>21.6</td> <td>22.35</td> <td>0.821</td> <td>0.850</td> <td>0.880</td> </tr> <tr> <td>H</td> <td>30.85</td> <td>31.6</td> <td>32.35</td> <td>1.215</td> <td>1.244</td> <td>1.274</td> </tr> <tr> <td>I</td> <td>23</td> <td>23.5</td> <td>24</td> <td>0.906</td> <td>0.925</td> <td>0.945</td> </tr> <tr> <td>J</td> <td>0.25</td> <td>0.75</td> <td>1.25</td> <td>0.010</td> <td>0.030</td> <td>0.049</td> </tr> <tr> <td>K</td> <td>10.5</td> <td>11</td> <td>11.5</td> <td>0.413</td> <td>0.433</td> <td>0.453</td> </tr> <tr> <td>L</td> <td>6.5</td> <td>7</td> <td>7.5</td> <td>0.256</td> <td>0.276</td> <td>0.295</td> </tr> <tr> <td>M</td> <td>49.5</td> <td>50</td> <td>50.5</td> <td>1.949</td> <td>1.989</td> <td>1.988</td> </tr> <tr> <td>N</td> <td>51</td> <td>51.5</td> <td>52</td> <td>2.008</td> <td>2.028</td> <td>2.047</td> </tr> <tr> <td>O</td> <td>62.25</td> <td>63</td> <td>63.75</td> <td>2.451</td> <td>2.480</td> <td>2.510</td> </tr> <tr> <td>P</td> <td>10.25</td> <td>11</td> <td>11.75</td> <td>0.404</td> <td>0.433</td> <td>0.463</td> </tr> <tr> <td>Q</td> <td>5.6</td> <td>6.1</td> <td>6.6</td> <td>0.220</td> <td>0.240</td> <td>0.260</td> </tr> <tr> <td>R</td> <td>0.3</td> <td>0.5</td> <td>0.7</td> <td>0.012</td> <td>0.020</td> <td>0.028</td> </tr> <tr> <td>S</td> <td>2.55</td> <td>2.75</td> <td>2.95</td> <td>0.100</td> <td>0.108</td> <td>0.116</td> </tr> <tr> <td>T</td> <td>0.25</td> <td>0.75</td> <td>1.25</td> <td>0.010</td> <td>0.030</td> <td>0.049</td> </tr> <tr> <td>U</td> <td>10.5</td> <td>11</td> <td>11.5</td> <td>0.413</td> <td>0.433</td> <td>0.453</td> </tr> <tr> <td>V</td> <td>6.5</td> <td>7</td> <td>7.5</td> <td>0.256</td> <td>0.276</td> <td>0.295</td> </tr> <tr> <td>W</td> <td>10.5</td> <td>11</td> <td>11.5</td> <td>0.413</td> <td>0.433</td> <td>0.453</td> </tr> </tbody> </table>							Ref	Dimensions						Millimeters			Inches				Min	Typ	Max	Min	Typ	Max	A	2.85	3	3.15	0.112	0.118	0.124	B	2.3	2.5	2.7	0.091	0.098	0.106	C	1.9	2.1	2.3	0.075	0.083	0.091	D			6			0.236	E	16.25	17	17.75	0.640	0.669	0.699	F	0.4	0.5	0.6	0.016	0.020	0.024	G	20.85	21.6	22.35	0.821	0.850	0.880	H	30.85	31.6	32.35	1.215	1.244	1.274	I	23	23.5	24	0.906	0.925	0.945	J	0.25	0.75	1.25	0.010	0.030	0.049	K	10.5	11	11.5	0.413	0.433	0.453	L	6.5	7	7.5	0.256	0.276	0.295	M	49.5	50	50.5	1.949	1.989	1.988	N	51	51.5	52	2.008	2.028	2.047	O	62.25	63	63.75	2.451	2.480	2.510	P	10.25	11	11.75	0.404	0.433	0.463	Q	5.6	6.1	6.6	0.220	0.240	0.260	R	0.3	0.5	0.7	0.012	0.020	0.028	S	2.55	2.75	2.95	0.100	0.108	0.116	T	0.25	0.75	1.25	0.010	0.030	0.049	U	10.5	11	11.5	0.413	0.433	0.453	V	6.5	7	7.5	0.256	0.276	0.295	W	10.5	11	11.5	0.413	0.433	0.453
Ref	Dimensions																																																																																																																																																																																										
	Millimeters			Inches																																																																																																																																																																																							
	Min	Typ	Max	Min	Typ	Max																																																																																																																																																																																					
A	2.85	3	3.15	0.112	0.118	0.124																																																																																																																																																																																					
B	2.3	2.5	2.7	0.091	0.098	0.106																																																																																																																																																																																					
C	1.9	2.1	2.3	0.075	0.083	0.091																																																																																																																																																																																					
D			6			0.236																																																																																																																																																																																					
E	16.25	17	17.75	0.640	0.669	0.699																																																																																																																																																																																					
F	0.4	0.5	0.6	0.016	0.020	0.024																																																																																																																																																																																					
G	20.85	21.6	22.35	0.821	0.850	0.880																																																																																																																																																																																					
H	30.85	31.6	32.35	1.215	1.244	1.274																																																																																																																																																																																					
I	23	23.5	24	0.906	0.925	0.945																																																																																																																																																																																					
J	0.25	0.75	1.25	0.010	0.030	0.049																																																																																																																																																																																					
K	10.5	11	11.5	0.413	0.433	0.453																																																																																																																																																																																					
L	6.5	7	7.5	0.256	0.276	0.295																																																																																																																																																																																					
M	49.5	50	50.5	1.949	1.989	1.988																																																																																																																																																																																					
N	51	51.5	52	2.008	2.028	2.047																																																																																																																																																																																					
O	62.25	63	63.75	2.451	2.480	2.510																																																																																																																																																																																					
P	10.25	11	11.75	0.404	0.433	0.463																																																																																																																																																																																					
Q	5.6	6.1	6.6	0.220	0.240	0.260																																																																																																																																																																																					
R	0.3	0.5	0.7	0.012	0.020	0.028																																																																																																																																																																																					
S	2.55	2.75	2.95	0.100	0.108	0.116																																																																																																																																																																																					
T	0.25	0.75	1.25	0.010	0.030	0.049																																																																																																																																																																																					
U	10.5	11	11.5	0.413	0.433	0.453																																																																																																																																																																																					
V	6.5	7	7.5	0.256	0.276	0.295																																																																																																																																																																																					
W	10.5	11	11.5	0.413	0.433	0.453																																																																																																																																																																																					

Ordering Information

<p>AK</p> <p>Aiko Electronics Technology Co., LTD</p>	<p>152</p> <p>$I_{T(RMS)}=150A$</p>	<p>KQ</p> <p>Module of anti-parallel of SCRs</p>	<p>-22</p> <p>18: $V_{DSM}/V_{RSM} \geq 1900V$ 20: $V_{DSM}/V_{RSM} \geq 2100V$ 22: $V_{DSM}/V_{RSM} \geq 2300V$</p>
--	---	---	--